



Overview

RC-4HC is Elitech conventional Temperature/Humidity data loggers, support external Temperature sensor and buzzer alarms. It is world-wide remote acess to various applications like Life Sciences, Food, Shipping, Logistics, & Pharmaceutical Industries.

F© (€ UN38.3 DO \$\rightarrow\$160

Features

- > Internal Temperature/Humidity sensor, accuracy up to ±0.5°C, ±3%RH
- Double alarm thresholds configurable with buzzer alarm notification
- USB cable included, no reader required to connect with PC and ElitechLog software
- External T emperature sensors applicable to various scenarios (optional)
- Wall-mounted in various locations with multiple mounting hardware(optional)

Technical Specifications	RC-4HC
Recording Options	Multi-Use
Temperature Range	-30°C to 70°C (Internal sensor) -40°C to 85°C (optional external sensor)
Humidity Range	0~100% RH
Temperature Accuracy	±0.5°C(-20°C/+40°C) +1.0°C(other range)
Humidity Accuracy	±3%RH(25°C,20%RH to 90%RH) +5%RH(other range)
Resolution	0.1°C,0.1%RH
Data Storage Capacity	16,000 readings
Shelf Life/Battery	1 year'/CR2450 button cell
Recording Interval	15 minutes(standard, others on request)
Report Generation	PDF&Excel report by Elitech software
Alarm Configuration	Optional, only 2 points
Reprogrammable	With free Elitech Win or MAC software
Startup Mode	Button
Stop Mode	Button, software or stop when full

RC-4HC: Depending on optimal storage conditions (15°C to 23°C/45% to 75% RH)

Temp | Humidity | Pressure | Differential Pressure | Vacuum | Gases | Particle | Air Flow Moisture | Dissolved Oxygen | Radiation | Air Quality | Light / Lux | Distance | Vibration

Instrukart Holdings

Ph: +91 (40)40262020 | Mob: +91 88865 50506; Email: info@instrukart.com | www.instrukart.com



